



Alcohol Wipes

Safety Data Sheet

SDS

BSW2412, Isopropyl Alcohol Wipes


SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME	Isopropyl Alcohol Wipes	DESCRIPTION: Non-woven saturated with 70% Isopropyl Alcohol
Recommended Use:	For disinfecting on hard, non-porous surfaces	
Supplier Name:	Bastion Pacific Pty Ltd	
Supplier Address:	8 Montore Road, Minto NSW 2566	

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS (Specific Chemical Identity: Common Names)	CAS #	% By Volume	Classification
Isopropyl Alcohol	67-63-0	70%	Eye Damage/Irritation - Category 2, H319 Highly Flammable Liquid and Vapor - category 2, H225 Specific target Organ Toxicity - Single Exposure - Category 3, H336
Water	7732-18-5	30%	NOT APPLICABLE

SECTION 3 - HAZARDS IDENTIFICATION (Potential Health Effects)

Classification	<ul style="list-style-type: none"> - Eye Damage/Irritation - Category 2, H319 - Highly Flammable Liquid and Vapor - category 2, H225 - Specific target Organ Toxicity - Single Exposure - Category 3, H336
Signal Word	
Pictogram	Cause serious eye irritation
Hazard Statements	Highly Flammable Liquid and Vapor
EYE:	Cause serious eye irritation
SKIN:	<ul style="list-style-type: none"> - Low toxicity - Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis
INHALATION (BREATHING):	Vapor concentrations above recommended exposure levels may be irritating to the eyes and respiratory tract, may cause headaches and dizziness, could be anesthetic and may have other central nervous system effects
INGESTION (SWALLOWING):	Small amount of liquid aspirated into the respiratory system during ingestion or from vomiting may cause pneumonia or pulmonary edema.
SIGNS AND SYMPTOMS:	Take by mouth may cause nausea, vomiting, stomach pains, diarrhea, coma or death
CANCER:	N/A
TARGET ORGANS:	N/A
DEVELOPMENTAL:	N/A
OTHER COMMENTS:	N/A
PRE-EXISTING MEDICAL CONDITIONS:	N/A

SDS	BSW2412, Isopropyl Alcohol Wipes
------------	---

SECTION 4 - FIRST AID MEASURES

EYES CONTACT:	Immediately flush eyes with large amount of water for at least 15 minutes while holding eyelids open. Get prompt medical attention.
SKIN CONTACT:	Rinse/Flush with large amounts of water for 15-20minutes; use available soap; if irritation persists or if concerned, seek medical attention. Remove grossly contaminated clothing, including shoes, and launder before reuse.
INHALATION (BREATHING):	Using proper respiratory protection, immediately remove the affected victim from exposure to fresh air and keep at rest in a position comfortable for breathing. Administrator artificial respiration if breathing is stopped. Call for prompt medical attention.
INGESTION (SWALLOWING):	If swallowed, call a physician immediately. Rinse mouth and throat thoroughly with water. Do not induce vomiting unless directed by a physician. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.
MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:	Shortness of breath, irritation, nausea, headache
INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	If seeking medical attention, provide SDS document to physician. Physician should treat symptomatically.

SECTION 5 - FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:	<ul style="list-style-type: none"> - Flash Point: 21 degree celsius - OSHA Flammability Class: 3 - LEL/UEL: 2.0/12.7(vol%) - Auto ignition Temperature: 399 degree celsius
UNUSUAL FIRE & EXPLOSION HAZARDS:	N/A
SUITABLE EXTINGUISHING MEDIA:	<ul style="list-style-type: none"> - In case of fire, use Dry Chemical, Chemical foam, Alcohol - resistant foam, Carbon Dioxide (CO2). - Water spray can be used to dilute spills to nonflammable mixtures.
SUITABLE EXTINGUISHING MEDIA:	Water may be ineffective but should be used to cool fire - exposed structures and vessels. DO NOT USE: Direct water stream.
FIREFIGHTING INSTRUCTIONS:	<ul style="list-style-type: none"> - Protective equipment: - Wear protective eyewear, gloves, and clothing. Refer to section 8 - Additional information (precautions): <p>Ensure adequate ventilation. Avoid contact with skin, eyes, and clothing. Do not inhale gases, fumes, dust, mist, vapor, and aerosols. Use non - sparking tools and intrinsically safe equipment.</p>

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:	Keep away from ignition sources. Protect from heat.
ENVIRONMENTAL PRECAUTIONS:	Do not flush into surface water or sanitary sewer system. Should not be released into the environment
FALMMABLE SMALL SPILL:	Absorb with an inert dry material and place in an appropriate waste disposal container.

SDS	BSW2412, Isopropyl Alcohol Wipes
------------	---

FLAMMABLE LARGE SPILL:	Flammable liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with dry earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas.
-------------------------------	---

SECTION 7 - HANDLING AND STORAGE	
---	--

HANDLING FLAMMABLE:	Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/vapor/spray. Avoid contact with eyes. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Keep away from incompatibles, such as oxidizing agents, acids.
----------------------------	--

STORAGE FLAMMABLE:	Store in a cool location. Store securely in flammable storage area away from sources of ignition. Do not store in Temperatures > 122°F. Provide ventilation for containers. Avoid storage near extreme heat, ignition sources or open flame. Keep container tightly sealed. Protect from freezing and physical damage. Store away from incompatible materials.
---------------------------	--

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION	
--	--

ENGINEERING CONTROLS:	The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures or otherwise to maintain ambient concentration below the recommended threshold exposure limited. Use explosion-proof ventilation equipment.
------------------------------	---

RESPIRATORY PROTECTION:	Where concentrations in air may exceed the limits given in this section, it is recommended to use a half face filter mask to protect from overexposure by inhalation. Suitable filter material depends on the amount and type of chemicals being handled in the workplace, but filter material of type "A" or similar may be considered for use.
--------------------------------	--

SKIN PROTECTION:	The use and choice of personal protection equipment is related to the hazard of the product, the workplace, and the way the product is handled. In general, we recommend as a minimum safety precaution that safety glasses with side shields and workclothes protecting arms, legs and body be used. In addition, any person visiting an area where this product is handled at processed should at least wear safety glasses with side-shields.
-------------------------	--

EYE/FACE PROTECTION:	When handling this product, it is recommended to wear splash resistant goggles.
-----------------------------	---

OTHER WORK/HYGIENIC PRACTICE:	No smoking. Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.
--------------------------------------	---

SECTION 9 - PHYSICAL / CHEMICAL PROPERTIES	
---	--

Note: Unless otherwise stated, values are determined at 20 degrees Celsius (68 degrees Fahrenheit) and 760 mm Hg (1 atm)

FLASH POINT:	12 degree celsius
FLAMMABLE/EXPLOSIVE LIMITS(%):	LEL/UEL:2.0/12.7 vol%
AUTO IGNITION TEMPERATURE:	399 degree celsius
COLOUR:	Clear, colourless with characteristic of IPA
SOLUBILITY:	Azeotrope

SDS	BSW2412, Isopropyl Alcohol Wipes
------------	---

FLAMMABILITY:	Flammable
PHYSICAL STATE:	Solid
ODOUR:	Isopropyl Alcohol Odour
pH:	N/A
VAPOR PRESSURE (kPa):	33 mmHg
BOILING POINT:	Not determined
FREEZING/MELTING POINT:	-88.5 degree celsuis
SOLUBILITY IN WATER:	N/A
SPECIFIC GRAVITY:	N/A
EVAPORATION RATE (nBuAc+1):	2.5

SECTION 10 - STABILITY & REACTIVITY

CHEMICAL STABILITY:	No decomposition if used and stored according to specifications. Stable under normal conditions.
CONDITIONS TO AVOID:	Incompatible materials.
INCOMPATIBLE (MATERIALS TO AVOID):	Strong Oxidizing agents, acids, acid anhydride, halogen
INCOMPATIBLE (MATERIALS TO AVOID):	Heat Sparks
INCOMPATIBLE (MATERIALS TO AVOID):	Open flames, Will attach some forms of rubber, plastics and coatings. May react
HAZARDOUS DECOMPOSITION OR BYPRODUCTS:	Toxic oxides of carbon, acrid and irritating fumes
HAZARDOUS POLYMERIZATION:	N/A

SECTION 11 - TOXICOLOGICAL INFORMATION

ACUTE TOXICITY: DERMAL	N/A
ACUTE TOXICITY: ORAL(RAT) Id50:	5045mg/kg
ACUTE TOXICITY: INHALATION	N/A
CHRONIC TOXICITY	N/A
CORROSION IRRITATION	N/A
SPECIFIC TARGET ORGAN	N/A
CARCINOGENICITY	N/A
MUTAGENICITY	N/A
REPRODUCTIVE TOXICITY	N/A

SECTION 12 - ECOLOGICAL INFORMATION

ECOTOXICITY:	N/A
--------------	-----

SDS	BSW2412, Isopropyl Alcohol Wipes
------------	---

PRESISTENCE AND DEGRADABILITY	N/A
BIOACCUMULATIVE POTENTIAL:	N/A
MOBILITY IN SOIL:	N/A
OTHER ADVERSE EFFECTS:	This product has acute toxicity with effects of death in animals and low growth rates and death in plants. Chronic toxic effects, may be shortened life span, lower fertility, reproductive problems, and changes in appearance and/or behavior in animals

SECTION 13 - DISPOSABLE CONSIDERATIONS

WASTE DISPOSAL:	It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities. Remove all sources of ignition. Do not flush to sewer. Have fire extinguishing agent available in case of fire. Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations. Ensure complete and accurate classification.
-----------------	---

SECTION 14 - TRANSPORT INFORMATION

DANGEROUS GOODS CODE:	32064
UN CODE:	1219
UN PROPER SHIPPING NAME:	N/A
DOT CLASSIFICATION:	ORM-D Limited Quantity
PACKING GROUP:	52

SECTION 15 - REGULATORY INFORMATION

GOVERNING DIRECTIVE:	Dangerous Substances Directive 67/548/EC, as modified.
----------------------	--

Warning: S07/09 Keep container tightly closed and in a well ventilated place
 S16 Keep away from sources of ignition. No Smoking
 S24/25 Avoid contact with skin and eyes.
 S26 In case of contact with eyes, flush immediately with plenty of water and seek medical advice
 S33 Take precautionary measures against static discharges
 S43B In case of fire, use Dry Chemical, Chemical foam, Alcohol-resistant foam, Carbon Dioxide (CO2).

SECTION 16 - OTHER INFORMATION

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES	The product information contained in this Safety Data Sheet was collected from various supplier sources. All product claims and specifications are those of Bastion Pacific Pty Ltd's suppliers and may not have been independently verified by Bastion Pacific. Bastion Pacific is not responsible for errors or omissions in, or completeness of the product information. BASTION PACIFIC PTY LTD DISCLAIMS ALL WARRANTIES OF ANY KIND OR NATURE, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF THE SUITABILITY OR FITNESS OF ANY PRODUCT FOR A PARTICULAR PURPOSE
--	--