VIRTUE +

Alcohol Plus Hand Gel

Safety Data Sheet

Phone: 1300 255 546 Email: sales@virtueplus.com.au



Connect online @ Virtue Plus



Chemwatch Hazard Alert Code: 3

Issue Date: 01.06.2024 Print Date: 01.06.2024

L.GHS.AUS.EN

Alcohol Plus Hand Gel

Nowchem

Version No: **1.2** Safety Data Sheet according to WHS and ADG requirements

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Alcohol Plus Hand Gel
Synonyms	Not Available
Proper shipping name	ALCOHOLS, N.O.S.
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

sales@nowchem.com.au

Relevant identified uses	For use on hands to reduce bacteria and stop spread of germs.
Details of the supplier of the safety data sheet	
Registered company name	Nowchem
Address	112A Albatross Road NSW Australia
Telephone	(02) 4421 4099
Fax	(02) 4421 4932
Website	www.nowchem.com.au

Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	(02) 4421 4099
Other emergency telephone numbers	0413 809 255

SECTION 2 HAZARDS IDENTIFICATION

Email

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	3		
Toxicity	0		0 = Minimum
Body Contact	0		1 = Low
Reactivity	1		3 = High
Chronic	0		4 = Extreme

Poisons Schedule	Not Applicable
Classification ^[1]	Flammable Liquid Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Issue Date: 01.06.2024 Print Date: 01.06.2024

Alcohol Plus Hand Gel

GHS label elements	
SIGNAL WORD	DANGER
Hazard statement(s)	
H225	Highly flammable liquid and vapour.
Precautionary statement(s)) Prevention
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statement(s)) Response
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam for extinction.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
Precautionary statement(s) Storage	
P403+P235	Store in a well-ventilated place. Keep cool.
Precautionary statement(s) Disposal
P501	Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
64-17-5	>60	ethanol

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For acute or short term repeated exposures to ethanol:

- Acute ingestion in non-tolerant patients usually responds to supportive care with special attention to prevention of aspiration, replacement of fluid and correction of nutritional deficiencies (magnesium, thiamine pyridoxine, Vitamins C and K).
- Give 50% dextrose (50-100 ml) IV to obtunded patients following blood draw for glucose determination.
- Comatose patients should be treated with initial attention to airway, breathing, circulation and drugs of immediate importance (glucose, thiamine).
- Decontamination is probably unnecessary more than 1 hour after a single observed ingestion. Cathartics and charcoal may be given but are probably not effective in single ingestions.
- Fructose administration is contra-indicated due to side effects.

Page 3 of 9

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result	
Advice for firefighters		
Fire Firebiling		

Fire Fighting	
Fire/Explosion Hazard	 Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat, flame and/or oxidisers. Vapour may travel a considerable distance to source of ignition. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include; carbon dioxide (CO2) other pyrolysis products typical of burning organic material

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb small quantities with vermiculite or other absorbent material. Wipe up. Collect residues in a flammable waste container.
Major Spills	

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling		
Safe handling	 Containers, even those that have been emptied, may contain explosive vapours. Do NOT cut, drill, grind, weld or perform similar operations on or near containers. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. Avoid smoking, naked lights, heat or ignition sources. When handling, DO NOT eat, drink or smoke. Vapour may ignite on pumping or pouring due to static electricity. DO NOT use plastic buckets. Earth and secure metal containers when dispensing or pouring product. Use spark-free tools when handling. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions. 	
Other information	 Store in original containers in approved flame-proof area. No smoking, naked lights, heat or ignition sources. DO NOT store in pits, depressions, basements or areas where vapours may be trapped. Keep containers securely sealed. Store away from incompatible materials in a cool, dry well ventilated area. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS. 	

Conditions for safe storage, including any incompatibilities

Packing as supplied by manufacturer.

	Plastic containers may only be used if approved for flammable liquid.
	 Check that containers are clearly labelled and free from leaks.
	For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
	▶ For materials with a viscosity of at least 2680 cSt. (23 deg. C)
	▶ For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
	Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with
	friction closures and (iii) low pressure tubes and cartridges may be used.
	Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages
	In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.
Storage incompatibility	 Avoid oxidising agents, acids, acid chlorides, acid anhydrides, chloroformates. Avoid strong bases.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	name TWA			STEL Peak			Notes
Australia Exposure Standards	ethanol	Ethyl alcohol 1880 mg/m3 / 1000 ppm			Not Available	Not Availab	le	Not Available	
EMERGENCY LIMITS									
Ingredient	Material name			TEEL-1		TEEL-2		TEEL-3	
ethanol	Ethyl alcohol; (Ethanol)			Not Available		Not Available		Not Available	
Ingredient	Original IDLH			Revised IDLH					
ethanol	15,000 ppm			3,300 [LEL] ppm					

MATERIAL DATA

For ethanol:

Odour Threshold Value: 49-716 ppm (detection), 101 ppm (recognition)

Eye and respiratory tract irritation do not appear to occur at exposure levels of less than 5000 ppm and the TLV-TWA is thought to provide an adequate margin of safety against such effects. Experiments in man show that inhalation of 1000 ppm caused slight symptoms of poisoning and 5000 ppm caused strong stupor and morbid sleepiness. Subjects exposed to 5000 ppm to 10000 ppm experienced smarting of the eyes and nose and coughing. Symptoms disappeared within minutes. Inhalation also causes local irritating effects to the eyes and upper respiratory tract, headaches, sensation of heat intraocular tension, stupor, fatigue and a need to sleep. At 15000 ppm there was continuous lachrymation and coughing.

for triethanolamine:

Exposure at or below the TLV-TWA is thought to minimise the potential for skin and eye irritation, and acute effects (including liver, kidney and nerve damage) and chronic effects (including cancer and allergic contact dermatitis).

Odour Safety Factor (OSF)

OSF=0.77 (triethanolamine)

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.
Personal protection	
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]
Skin protection	See Hand protection below
Hands/feet protection	Generally not required.
Body protection	See Other protection below

Alcohol	Plus	Hand	Gel	

Other protection	 Eyewash unit. Ensure there is ready access to a safety shower. Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. For large scale or continuous use wear tight-weave non-staticclothing (no metallic fasteners, cuffs or pockets). Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductivecompound chemically bound to the bottom components, for permanent control toelectricially ground the foot an shall dissipate static electricity from thebody to reduce the possibility of ignition of volatile compounds. Electricalresistance must range between 0 to 500,000 ohms. Conductive shoes should bestored in lockers close to the room in which they are worn. Personnel who havebeen issued conductive footwear should not wear them from their place of workto their homes and return.
Thermal hazards	Not Available

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Clear Viscous Gel		
Physical state	Gel	Relative density (Water = 1)	0.885 - 0.895
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	6 - 8	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Flammable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not Nevertheless, good Exposure to aliphat weakness, delirium involvement may p pneumonitis and br Kidney and liver da structures that lack (diols) rarely repres irritation which, in to	is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). s, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. aliphatic alcohols with more than 3 carbons may produce central nervous system effects such as headache, dizziness, drowsiness, muscle elirium, CNS depression, coma, seizure, and neurobehavioural changes. Symptoms are more acute with higher alcohols. Respiratory tract may produce irritation of the mucosa, respiratory insufficiency, respiratory depression secondary to CNS depression, pulmonary oedema, chemical and bronchitis. Cardiovascular involvement may result in arrhythmias and hypotension. Gastrointestinal effects may include nausea and vomiting. iver damage may result following massive exposures. The alcohols are potential irritants being, generally, stronger irritants than similar organic at lack functional groups (e.g. alkanes) but are much less irritating than the corresponding amines, aldehydes or ketones. Alcohols and glycols represent serious hazards in the workplace, because their vapour concentrations are usually less than the levels which produce significant ch, in turn, produce significant central nervous system effects as well.			
	Ingestion of ethanc	I may produce nausea, vomiting, gastrointestinal bleeding, abdominal pain and diarrhoea. Systemic effects:			
Induction	Blood concentration:	Effects:			
ingestion	<1.5 g/l	Mild: Impaired visual acuity, coordination and reaction time, emotional lability			
	1.5-3.0 g/l	Moderate: Slurred speech, confusion, ataxia, emotional lability, perceptual and sensation disturbances possible blackout spells, and incoordination with impaired objective performance in standardised tests. Possible diplopia, flushing, tachycardia, sweating and incontinence.			

		Bradypnoea may occur early and tachypnoea may develop	in cases of metab	pollic acidosis, hypoglycaemia and hypokalaemia.	
	3-5 g/l	Severe: Cold clammy skin, hypothermia and hypotension. Atrial fibrillation and atrioventricular block have been repo Respiratory depression may occur, respiratory failure may and pulmonary oedema. Convulsions due to severe hypoglycaemia may also occur Acute hepatitis may develop.	rted. follow serious inte	oxication, aspiration of vomitus may result in pneumonitis	
	The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.				
Skin Contact	Skin contact is not t through wounds, le Limited evidence es following direct con being present twen result in a form of c progress to blisterin the skin (spongiosis Most liquid alcohols	hought to have harmful health effects (as classified under Er sions or abrasions. kists, or practical experience predicts, that the material either tact, and/or produces significant inflammation when applied to y-four hours or more after the end of the exposure period. St ontact dermatitis (nonallergic). The dermatitis is often charan ig (vesiculation), scaling and thickening of the epidermis. At s) and intracellular oedema of the epidermis. s appear to act as primary skin irritants in humans. Significar	C Directives); the r produces inflamm o the healthy intar in irritation may al terised by skin re the microscopic le the percutaneous al	material may still produce health damage following entry nation of the skin in a substantial number of individuals ct skin of animals, for up to four hours, such inflammation lso be present after prolonged or repeated exposure; this may dness (erythema) and swelling (oedema) which may evel there may be intercellular oedema of the spongy layer of bsorption occurs in rabbits but not apparently in man.	
Eye	Although the mater characterised by te	ial is not thought to be an irritant (as classified by EC Directiv aring or conjunctival redness (as with windburn).	ves), direct contac	t with the eye may produce transient discomfort	
Chronic	Practical experienc of producing a posi Long-term exposur Repeated ingestion described as foetal disorders and redu	e shows that skin contact with the material is capable either ive response in experimental animals. e to ethanol may result in progressive liver damage with fibro of ethanol by pregnant women may adversely affect the cen alcohol syndrome. These include mental and physical retard ced head size.	of inducing a sens sis or may exacer ral nervous syster lation, learning dis	itisation reaction in a substantial number of individuals, and/or bate liver injury caused by other agents. m of the developing foetus, producing effects collectively sturbances, motor and language deficiency, behavioural	
Alcobol Plus Hand Gal	TOXICITY		IRRITATION		
Alconor Plus Hand Ger	Not Available		Not Available		
	TOXICITY		IRRITATIO	N	
	Dermal (rabbit) L	050: 17100 mg/kg ^[1]	Eye (rabbit)	: 500 mg SEVERE	
ethanol	Inhalation (rat) LC	50: 64000 ppm/4hr ^[2]	Eye (rabbit)	:100mg/24hr-moderate	
	Oral (rat) LD50: >	1187-2769 mg/kg ^[1]	Skin (rabbit)):20 mg/24hr-moderate	
			Skin (rabbit):400 mg (open)-mild	
Legend:	1. Value obtained fi extracted from RTE	om Europe ECHA Registered Substances - Acute toxicity 2. ECS - Register of Toxic Effect of chemical Substances	* Value obtained f	from manufacturer's SDS. Unless otherwise specified data	
Alcohol Plus Hand Gel	The following inforr Contact allergies qu a cell-mediated (T I reactions. The sign for contact with it ar sensitising potentia reaction in more that	nation refers to contact allergens as a group and may not be uickly manifest themselves as contact eczema, more rarely a ymphocytes) immune reaction of the delayed type. Other alle fficance of the contact allergen is not simply determined by it e equally important. A weakly sensitising substance which is I with which few individuals come into contact. From a clinica an 1% of the persons tested.	specific to this pr s urticaria or Quin rgic skin reactions s sensitisation pol widely distributed I point of view, sul	oduct. acke's oedema. The pathogenesis of contact eczema involves s, e.g. contact urticaria, involve antibody-mediated immune tential: the distribution of the substance and the opportunities d can be a more important allergen than one with stronger bstances are noteworthy if they produce an allergic test	
Acute Toxicity	\otimes	c	arcinogenicity	0	
Skin Irritation/Corrosion	\otimes	F	Reproductivity	0	
Serious Eye Damage/Irritation	\odot	STOT - Si	ngle Exposure	\odot	
Respiratory or Skin sensitisation	\otimes	STOT - Repea	ated Exposure	0	
Mutagenicity	0	Asp	iration Hazard	0	
			Legend: X	 Data available but does not fill the criteria for classification Data required to make classification available 	

 \odot – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
ethanol	EC50	24	Algae or other aquatic plants	0.0129024mg/L	4
ethanol	EC50	48	Crustacea	2mg/L	4

ethanol	LC50	96	Fish	42mg/L	4	
ethanol	NOEC	2016	Fish	0.000375mg/L	4	
ethanol	EC50	72	Algae or other aquatic plants	275mg/L	2	
Legend:	Extracted from 1. IUCLI Aquatic Toxicity Data (E Bioconcentration Data 7	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3. 12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconceptration Data 8. Vendor Data				

When ethanol is released into the soil it readily and quickly biodegrades but may leach into ground water; most is lost by evaporation. When released into water the material readily evaporates and is biodegradable.

Ethanol does not bioaccumulate to an appreciable extent.

The material is readily degraded by reaction with photochemically produced hydroxy radicals; release into air will result in photodegradation and wet deposition.

Environmental Fate:

TERRESTRIAL FATE: An estimated Koc value of 1 indicates that ethanol is expected to have very high mobility in soil. Volatilisation of ethanol from moist soil surfaces is expected to be an important fate process given a Henry's Law constant of 5X10-6 atm-m3/mole. The potential for volatilisation of ethanol from dry soil surfaces may exist based upon an extrapolated vapor pressure of 59.3 mmHg. Biodegradation is expected to be an important fate process for ethanol based on half-lives on the order of a few days for ethanol in sandy soil/groundwater microcosms. AQUATIC FATE: An estimated Koc value of 1 indicates that ethanol is not expected to adsorb to suspended solids and sediment. Volatilisation from water surfaces is expected based upon a Henry's Law constant of 5X10-6 atm-m3/mole. Using this Henry's Law constant and an estimation method, volatilisation half-lives for a model river and model lake are 3 and 39 days, respectively.An estimated BCF= 3, from a log Kow of -0.31 suggests bioconcentration in aquatic organisms is low. Hydrolysis and photolysis in sunlit surface waters is not expected to be an important environmental fate process for ethanol since this compound lacks functional groups that hydrolyse or absorb light under environmentally relevant conditions. Ethanol was degraded with half-lives on the order of a few days in aquatic studies conducted using microcosms constructed with a low organic sandy soil and groundwater, indicating it is unlikely to be persistent in aquatic environments(8).

ATMOSPHERIC FATE: Ethanol, which has an extrapolated vapor pressure of 59.3 mm Hg at 25 deg C, is expected to exist solely as a vapor in the ambient atmosphere. Vapour-phase ethanol is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be 5 days, calculated from its rate constant of 3.3X10-12 m3/molecule-sec at 25 deg C.

Ecotoxicity: log Kow: -0.31- -0.32 Half-life (hr) air: 144

Half-life (hr) Alf: 144 Half-life (hr) H2O surface water: 144 Henry's atm m3 /mol: 6.29E-06 BOD 5 if unstated: 0.93-1.67,63% COD: 1.99-2.11,97% ThOD: 2.1

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)

Bioaccumulative potential

Ingredient	Bioaccumulation
ethanol	LOW (LogKOW = -0.31)
Mobility in soil	

•	
Ingredient	Mobility
ethanol	HIGH (KOC = 1)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

	 Containers may still present a chemical hazard/ danger when empty.
	Return to supplier for reuse/ recycling if possible.
	Otherwise:
	If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then
	puncture containers, to prevent re-use, and bury at an authorised landfill.
	Where possible retain label warnings and SDS and observe all notices pertaining to the product.
	DO NOT allow wash water from cleaning or process equipment to enter drains.
Product / Packaging	It may be necessary to collect all wash water for treatment before disposal.
disposal	In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
-	Where in doubt contact the responsible authority.
	Recycle wherever possible.
	 Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
	 Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
	Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 TRANSPORT INFORMATION

Labels Required



Marine Pollutant

HAZCHEM	-3YE
Land transport (ADG)	
UN number	1987
UN proper shipping name	ALCOHOLS, N.O.S.
Transport hazard class(es)	Class3SubriskNot Applicable
Packing group	ll
Environmental hazard	Not Applicable
Special precautions for user	Special provisions274Limited quantity1 L

Air transport (ICAO-IATA / DGR)

UN number	1987	
UN proper shipping name	Alcohols, n.o.s. *	
Transport hazard class(es)	ICAO/IATA Class3ICAO / IATA SubriskNot ApplicableERG Code3L	
Packing group	П	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions Cargo Only Packing Instructions Cargo Only Maximum Qty / Pack Passenger and Cargo Packing Instructions Passenger and Cargo Maximum Qty / Pack Passenger and Cargo Limited Quantity Packing In Passenger and Cargo Limited Maximum Qty / Pac	A3A180 364 60 L 353 5 L structions Y341 1 L

Sea transport (IMDG-Code / GGVSee)

UN number	1987
UN proper shipping name	ALCOHOLS, N.O.S.
Transport hazard class(es)	IMDG Class3IMDG SubriskNot Applicable
Packing group	II
Environmental hazard	Not Applicable
Special precautions for user	EMS NumberF-E, S-DSpecial provisions274Limited Quantities1 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

ETHANOL(64-17-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards Australia Hazardous Substances Information System - Consolidated Lists

 National Inventory
 Status

 Australia - AICS
 Y

 Canada - DSL
 Y

Australia Inventory of Chemical Substances (AICS)

Continued...

Canada - NDSL	N (ethanol)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Υ
Japan - ENCS	Y
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at: www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index This document is copyright. Apart from any fair dealing for the purposes of privatestudy, research, review or criticism, as permitted under the Copyright Act, nopart may be reproduced by any process without written permission

fromCHEMWATCH. TEL (+61 3) 9572 4700.